



DOUBLE 2X6 WITH 2X4 ON EACH SIDE-FLOOR TO CEILING AT EACH FLOOR

ANCHOR LOCATIONS

DETAIL A SCALE 1 : 4

- Battery Powered: 24 VDC Control System
- Rated Load: 500 lbs
- Speed: 15 fpm
- Max. Travel: 21'-0"
- Winding Drum Drive with dual 1/4" aircraft cables
- Automatic up/down controls
- Key Lock on controls
- Emergency Stop Switch and Alarm
- Recessed Automatic LED Car Light
- Status LED Indicator
- Door Position switch on Sliding Car Door
- Slack Cable Safety Device with Switch
- Final Limit Switches

DESIGNED TO COMPLY WITH ASME A17.1 PART 5.3 WHEN PROPERLY INSTALLED

SECTION A-A SCALE 1 : 16

SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAYING HOME CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAYING HOME CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES			7/16/2019
TOLERANCES:		DRAWN	
FRACTIONAL: ±1/16		CHECKED	
ANGULAR: ±0.5°		ENG APPR.	
ONE PLACE DECIMAL ±0.1		MFG APPR.	
TWO PLACE DECIMAL ±0.01		Q.A.	
THREE PLACE DECIMAL ±0.005		PROJECT:	
INTERPRET GEOMETRIC TOLERANCING PER:			
MATERIAL			
FINISH			
DO NOT SCALE DRAWING			
CREST			
TITLE: EZ6 RIGHT SIDE ENTRY, LH CAR DOORS INSIDE SCH ENCLOSURE			
SIZE/WTG. NO.		REV	
B TYP - EZ6R-A-LH			
SCALE: 1:96		WEIGHT: SHEET 1 OF 1	